

**Sir Safety System S.p.A. Single-member company**  
Wholly-owned subsidiary of Sir Holding Srl  
Via dei Fornaciai, 9 - Santa Maria degli Angeli  
06081 Assisi - Perugia - Italy  
Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548  
Viale Europa 74  
20090 Cusago Milano  
Tel. +39 02.90394575 (R.A.)  
Fax +39 02.90394441

[export@sirsafety.com](mailto:export@sirsafety.com)  
[www.sirsafety.com](http://www.sirsafety.com)

COMPANY WITH  
QUALITY SYSTEM  
CERTIFIED BY DNV GL  
= ISO 9001 =



<b>Name: MSA Firefighter Helmet for Structural Fires</b>	<b>Code: 38301</b>	<b>Head Protection - MSA</b>
--	--------------------	------------------------------

### Description

The new F1XF helmet is ideal for structural fire-fighting in buildings, tunnels and other structures.  
Shell: high-temperature thermoplastic material, injection moulded.  
Shock absorption padding: polyurethane foam bumpers with reinforcement moulded in aramid.  
Flame resistant padded headband and chinstrap cover.  
Chinstrap: 3-point, adjustable with release buckle.  
Face shield: protective visor in thermoplastic with gold coating.  
Short-range lamp integrated for excellent visibility in dark and smoky environments.  
Weight: 1550 g.

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 443.  
It is classified as PPE Cat. III.



Category <b>III</b>	Colours Red, Yellow, Hi-Vis Yellow, Orange, Green.	Available Sizes Unica
Quantity/Carton <b>1</b>	Important Information Before use, ensure that the helmet is in perfect condition, that there are no significant defects on the surface of the cap, such as cracks, crevices, deep abrasions, discoloration or bruising; Once you become aware of a damage, you should immediately replace it.	Recommended for Structural firefighting in buildings and other structures; protection against fire, heat, falling of objects, smoke, chemicals' and molten metals' splashes.
Dexterity	EC Standards EN 443 CE	Storage and cleaning Keep in a cool dry place, far from heat sources and direct light.