

TECHNICAL SHEET

Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686 VAT Nr. IT 03359340548 Viale Europa 74 20090 Cusago Milano Tel. +39 02.90394575 (R.A.) Fax +39 02.90394441 export@sirsafety.com www.sirsafety.com

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL = ISO 9001 =



Name: FM3 Mask Code: 45359 Powered Air-Purifying Tornado System - Scott

Description

Full-face mask in accordance with EN 136. The side connection for the hose increases the wearer's comfort, whilst the design limits the pressure on the face. The panoramic visor maximizes the field of vision and the front-mounted diaphragm enables easy communication with other workers.

Minimum airflow: 140 l/m Assigned Protection Factor: 40 Nominal Protection Factor:2000 Actual hood weight: 600 g Noise Level: <65 dB (A) Hose Material: Polyurethane

Faceseal Material: Halogenated Butyl Rubber

Visor Material: Polycarbonate

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 12941. It is classified as PPE Cat. III.



Category	Colours	Available Sizes
III	Black	
Quantity/Carton	Important Information	Recommended for
1	The device cannot be considered a chemical protective clothing. Make sure the item is in good condition, undamaged before use. Once you become aware of a damage, you should immediately replace it.	
Dexterity	EC Standards EN 12941 CE	Storage and cleaning Keep in a cool dry place, far from heat sources.