

Sir Safety System S.p.A. Single-member company
Wholly-owned subsidiary of Sir Holding Srl
Via dei Fornaciai, 9 - Santa Maria degli Angeli
06081 Assisi - Perugia - Italy
Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548
Viale Europa 74
20090 Cusago Milano
Tel. +39 02.90394575 (R.A.)
Fax +39 02.90394441

export@sirsafety.com
www.sirsafety.com

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =



Name: Combined Shower and Eyewash Station	Code: 81131	Emergency Showers
--	--------------------	--------------------------

Description

Combined emergency shower and eyewash station. Operated by a rigid pull handle; aerated flow eyewash operated by push knob or pedal. Sprinklers: 10 inches diameter that ensures the water flow. The unit is connected to a source of flowing water, able of deliver the flow when all the components are operating simultaneously. It provides 76 l of water per minute. Wide area of the water flow: 50 cm at the center and 150 cm at the extremities. The valve is activated within a second. Easily localizable, accessible activator and not higher than 175 cm. Water sprinklers are protected from air pollutants. The unit is connected to a constant flow of water of 3 GPM. Eyewash: 11,5 inches in diameter. ABS bowl. Pipes and accessories in galvanized steel, pipes with anticorrosive polyethylene cover.

Sir emergency showers and eyewash conform to the EN 15154 CE standard. Among their characteristics, they feature a great flow of water, combined with a delicate jet, which, in the event of an accidental contamination with acids or corrosive chemicals, ensure an immediate and safe washing.



Category	Colours Green	Available Sizes
Quantity/Carton 1	Important Information Read carefully the user sheet included. Make sure the item is in good condition, undamaged before use. Once you become aware of a damage, you should immediately replace it.	Recommended for Ensures a quick and safe washing in case of accidental contact with acid or corrosive chemicals.
Dexterity	EC Standards EN 15154-1 EN 15154-2	Storage and cleaning Keep in a dry place, far from heat sources.