

Sir Safety System S.p.A. Single-member company
Wholly-owned subsidiary of Sir Holding Srl
Via dei Fornaciai, 9 - Santa Maria degli Angeli
06081 Assisi - Perugia - Italy
Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548
Viale Europa 74
20090 Cusago Milano
Tel. +39 02.90394575 (R.A.)
Fax +39 02.90394441

export@sirsafety.com
www.sirsafety.com

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =



Name: Gas Alert Quattro 3 Gas (LEL,O2,CO)	Code: 81632	Gas Detectors - BW
--	--------------------	---------------------------

Description

Gas Alert Quattro 3 Gas is rugged and reliable, it combines a comprehensive range of features with simple one-button operation.

- Detects up to 3 gases simultaneously (Fuels, Oxygen, Carbon Monoxide).
- It constantly shows the gas concentration on the display through icons for on-site auditing and compliance.
- IntelliFlash feature: continuous visual confirmation of detector operation and compliance through a flashing green light.
- Full function self-test of sensor, battery status, circuit integrity and audio/visual alarms.
- Impact and water resistant casing.
- Advanced microprocessors, and easily plug in/replaceable catalytic and electrochemical sensors.
- Low, high, TWA (Time Weighted Average), STEL (Short Term Exposure Limit) alarm for toxic gases and OL (Over Limit) alarm for combustible gases.
- Rechargeable batteries.
- Acoustic (95dB), visual (six red LED) and vibrating alarm.
- Compact 13.0 x 8.1 x 4.7 cm.
- Weight 316 g.

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 60079.
It is classified as PPE Cat. III.



Category III	Colours Yellow	Available Sizes
Quantity/Carton 1	Important Information Make sure the product is in good condition, undamaged and clean before use. Once you become aware of a damage, you should immediately replace it.	Recommended for Suitable to detect the presence of Fuels, Oxygen, Carbon Monoxide.
Dexterity	EC Standards EN 60079-0 EN 60079-11 EN 60079-26	Storage and cleaning Keep in a cool dry place, far from heat sources.